

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
19 May 2005 (19.05.2005)

PCT

(10) International Publication Number
WO 2005/045085 A1

- (51) International Patent Classification⁷: **C22C 38/00** 10-2004-0070959
(21) International Application Number: 10-2004-0079664 6 September 2004 (06.09.2004) KR
PCT/KR2004/002901 10-2004-0084298 6 October 2004 (06.10.2004) KR
21 October 2004 (21.10.2004) KR
(22) International Filing Date: 10 November 2004 (10.11.2004) (71) Applicant (for all designated States except US): POSCO [KR/KR]; 1 Koedong-dong, Nam-ku, Pohang, Kyungsangbook-do 790-300 (KR).
(25) Filing Language: Korean (72) Inventors; and
(26) Publication Language: English (75) Inventors/Applicants (for US only): YOON, Jeong-Bong [KR/KR]; c/o POSCO, 1 Koedong-dong, Nam-ku, Pohang, Kyungsangbook-do 790-785 (KR). SON, Won-Ho [KR/KR]; c/o POSCO, 1 Koedong-dong, Nam-ku, Pohang, Kyungsangbook-do 790-785 (KR). KANG, Ki-Bong [KR/KR]; c/o POSCO, 1 Koedong-dong, Nam-ku, Pohang, Kyungsangbook-do 790-785 (KR). CHO, Noi-Ha [KR/KR]; c/o Kwang-Yang Works, 700 Keumho-dong, Dongkwangyang, Chunlabook-do 545-090 (KR). PARK, Ki-Duck [KR/KR]; c/o Kwang-Yang Works, 700 Keumho-dong, Dongkwangyang, Chunlabook-do 545-090 (KR).
(30) Priority Data:
10-2003-0079050 10 November 2003 (10.11.2003) KR
10-2003-0082135 19 November 2003 (19.11.2003) KR
10-2003-0087566 4 December 2003 (04.12.2003) KR
10-2003-0087595 4 December 2003 (04.12.2003) KR
10-2003-0087534 4 December 2003 (04.12.2003) KR
10-2003-0088134 4 December 2003 (04.12.2003) KR
10-2003-0088134 5 December 2003 (05.12.2003) KR
10-2003-0088689 8 December 2003 (08.12.2003) KR
10-2003-0088521 8 December 2003 (08.12.2003) KR
10-2003-0088513 8 December 2003 (08.12.2003) KR
10-2003-0094485 22 December 2003 (22.12.2003) KR
10-2003-0099436 29 December 2003 (29.12.2003) KR
10-2003-0099352 29 December 2003 (29.12.2003) KR
10-2004-0041510 7 June 2004 (07.06.2004) KR
10-2004-0041511 7 June 2004 (07.06.2004) KR
10-2004-0041509 7 June 2004 (07.06.2004) KR
10-2004-0066620 24 August 2004 (24.08.2004) KR
10-2004-0070960 6 September 2004 (06.09.2004) KR
(74) Agent: C & S PATENT AND LAW OFFICE; C-2306 Daelim Acrotel, 467-6 Dogok-dong, Kangnam-gu, Seoul 135-971 (KR).
(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LU, MC, NL, PL, PT, RO, SE,

[Continued on next page]

(54) Title: COLD ROLLED STEEL SHEET HAVING AGING RESISTANCE AND SUPERIOR FORMABILITY, AND PROCESS FOR PRODUCING THE SAME

(57) Abstract: A cold rolled steel sheet, and a method of manufacturing the same, designed to have aging resistance and excellent formability suitable for use in automobile bodies, electronic appliances, and the like. The cold rolled steel sheet comprises 0.003 % or less of C, 0.003 ~ 0.03 % of S, 0.01 ~ 0.1 % of Al, 0.02 % or less of N, 0.2 % or less of P, at least one of 0.03 ~ 0.2 % of Mn and 0.005 ~ 0.2 % of Cu, and a balance of Fe and other unavoidable impurities in terms of weight%. When the steel sheet comprises one of Mn and Cu, the composition of Mn, Cu, and S satisfies at least one relationship: $0.58 * Mn / Sc$ 10 and $1 << 0.5 * Cu / S < 10$, and when the steel sheet comprises both Mn and Cu, the composition of Mn, Cu, and S satisfies the relationship: $Mn + Cu < 0.3$ and $2 < 0.5 * (Mn + Cu) / S << -20$. Participates of MnS, CuS, and (Mn, Cu)S have an average size of 0.2 μm or less. Since carbon content in a solid solution state in a crystal grain is controlled by fine precipitates of MnS, CuS, or (Mn, Cu)S, the steel sheet has enhanced aging resistance and formability, and has excellent yield strength and 15 strength-ductility.



WO 2005/045085 A1



SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

— with international search report